

RECEIVED
CENTRAL FAX CENTER

JAN 05 2007

FROMMER LAWRENCE & HAUG LLP

745 Fifth Avenue
New York, New York 10151
Telephone: (212) 588-0800
Facsimile: (212) 588-0500

FACSIMILE COVER LETTER

To: Examiner Justin E. Shepard
Art Unit 2617

Firm: U.S. Patent and Trademark Office

Facsimile No.: 571-273-8300

From: Paul A. Levy

Date: January 5, 2007

Re: Serial No. 09/890,894
Attorney Docket 450101-02897

No. of Pages: 13
(including cover page)

If you do not receive all pages or are unable to read the transmission, please call 212-588-0800.

CONFIDENTIALITY NOTICE

The documents accompanying this transmission contain confidential information intended for a specific individual and purpose. The information is private, and is legally protected by law. If you are not the intended recipient, you are hereby notified that any disclosure, copying, distribution, or the taking of any action in reliance on the contents of this facsimile is strictly prohibited.

00421029.DOC

PATENT
450101-02897

control for changing the type of the picture data output by said input/output means based on the profile information specifying the search results from said data reception side,

wherein the control means determines whether to modify the type of picture data from said outside to the input/output means based on whether the input/output means can accommodate the picture data,

wherein the control means does not transmit the picture data from the picture processing means based upon the profile as a premise for transmitting the picture data.

4. (Currently Amended) A data processing method comprising:

a step of processing picture signals input from outside to generate picture data;

a step of outputting the picture data generated as the picture data is comprehended in a packet conforming to the IEEE (The Institute of Electrical and Electronics Engineers) 1394 standard;

a step of generating a command packet for searching a profile coped with by picture data outputting destination to output the generated command packet to a data reception side;

a step of managing control for changing the type of the picture data output based on the profile information specifying the search results transmitted from said data reception side; and

a step of determining whether to transmit the picture data from said outside based on the profile information,

wherein the picture data from the outside is not transmitted based upon the profile as a premise for transmitting the picture data.

PATENT
450101-02897

5. (Currently Amended) A data transmission/reception system having a data transmission device and a data reception device; said data transmission device comprising:

first picture processing means for processing picture signals input from outside to generate picture data;

first input/output means for outputting the picture data generated by said first picture processing means to a picture reception device as the picture data generated is comprehended in a packet conforming to the IEEE (The Institute of Electrical and Electronics Engineers) 1394 standard; and

first control means for managing control for generating a command packet for searching a profile coded with by picture data reception device to output the generated command packet from said input/output means to said data reception device, said control means also managing control for changing the type of the picture data output by said first input/output means based on the profile information specifying the search results from a data reception side;

said data reception device including second input/output means for receiving picture data from said first input/output means as the picture data is comprehended in a packet conforming to the IEEE (The Institute of Electrical and Electronics Engineers) 1394 standard, and for outputting a response packet responsive to the command packet conforming to the IEEE (The Institute of Electrical and Electronics Engineers) 1394 standard from said first input/output means;

second picture processing means for performing pre-set picture processing using the picture data input by said ~~second~~ first picture processing means; and

second control means for controlling said second input/output means, responsive to inputting to said second input/output means of a command for searching a profile from said ~~first~~

PATENT
450101-02897

second input/output means means and for outputting the profile information indicating the profile coped with by said second picture processing means, as search results, to said data transmission device,

wherein the first control means does not transmit the picture data from the picture processing means based upon the profile as a premise for transmitting the picture data.

6. (Currently Amended) A data reception apparatus comprising:

a picture processing section for doing pre-set picture processing using television picture data from a television signal reception side;

an input/output section fed from said television signal reception side with said television picture data comprehended in an FCP (Function Control Protocol) packet conforming to the IEEE (The Institute of Electrical and Electronics Engineers) 1394 standard and for outputting a response packet responsive to a command packet conforming to the IEEE 1394 standard from the television signal reception side; and

a controller for controlling said input/output section to transmit to said television signal reception side profile information indicating a profile coped with by said picture processing section, as search results, responsive to the inputting of a version command packet for searching a profile of printable picture data to said input/output section,

wherein the controller determines whether to modify the type of picture data from the television signal reception side to the input/output section based on whether the input/output section can accommodate the picture data,

wherein the picture data from the television signal reception side is not transmitted based upon the profile as a premise for transmitting the picture data.

PATENT
450101-02897

7. (Currently Amended) A data transmission device comprising:
a picture processing section for picture-processing television data input from outside to generate picture data;
an input/output section for outputting the picture data generated by said picture processing section as the picture data is comprehended in an FCP (Function Control Protocol) packet conforming to the IEEE (The Institute of Electrical and Electronics Engineers) 1394 standard; and
a controller for managing control for generating a version command packet for searching a profile of printable picture data copied with by a data reception device as picture data outputting destination to output the generated version command packet from said input/output section to the data reception device side, said controller also managing control for changing the type of the picture data output by said input/output section based on profile information specifying the search results from said data reception device side,
wherein the television data from the picture processing section is not transmitted based upon the profile as a premise for transmitting the television data.